

**Product Details**

range name	HAYMAN
finish	SMOOTH
colours	CHARCOAL, LIMESTONE
product code   description	STANDARD UNIT

**Properties and Specifications**

actual dimensions (length x width x height mm)	390 X 245 X 198MM
dimensional category	-
average weight (KG)	24
durability class	General Purpose
number per sqm/lm	13
number per pallet	-
number per tonne	42
characteristics breaking load (kN)	>14
mean cold water absorption (%)	-
mean abrasion resistance (CM³)	-
characteristic unconfined compressive strength (MPa)	>13
	-

**Diagram**



*Tested as per AS/NZS 4456: 2003 and 4586: 2013.*

*This data represents average results from production lots based on the results achieved by samples selected at random for testing.  
Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification*

**Product Details**

range name	HAYMAN
finish	SMOOTH
colours	CHARCOAL, LIMESTONE
product code   description	CORNER UNIT

**Properties and Specifications**

actual dimensions (length x width x height mm)	360 X 160 X 198MM
dimensional category	-
average weight (KG)	17.2
durability class	General Purpose
number per sqm/lm	5
number per pallet	-
number per tonne	50
characteristics breaking load (kN)	-
mean cold water absorption (%)	-
mean abrasion resistance (CM <sup>3</sup> )	-
characteristic unconfined compressive strength (MPa)	>13
	-

**Diagram**



*Tested as per AS/NZS 4456: 2003 and 4586: 2013.*

*This data represents average results from production lots based on the results achieved by samples selected at random for testing.  
Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification*

**Product Details**

range name	HAYMAN
finish	SMOOTH
colours	CHARCOAL, LIMESTONE
product code   description	CAPPING UNIT

**Properties and Specifications**

actual dimensions (length x width x height mm)	390 X 245 X 90MM
dimensional category	-
average weight (KG)	16
durability class	General Purpose
number per sqm/lm	2.56
number per pallet	-
number per tonne	63
characteristics breaking load (kN)	-
mean cold water absorption (%)	-
mean abrasion resistance (CM <sup>3</sup> )	-
characteristic unconfined compressive strength (MPa)	>13
	-

**Diagram**



*Tested as per AS/NZS 4456: 2003 and 4586: 2013.*

*This data represents average results from production lots based on the results achieved by samples selected at random for testing.  
Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification*